

SCD2150



Power Rectifier Diodes

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

$I_{F(AV)}$	2160 A
V_{RRM}	200~1000 V
I_{FSM}	19 kA
I^2t	1805 $10^3 A^2s$

SYMBOL	CHARACTERISTIC	TEST CONDITIONS		$T_j(^{\circ}C)$	VALUE			UNIT
					Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Double side cooled,	$T_c=55^{\circ}C$	190			2550	A
			$T_c=85^{\circ}C$				2160	
V_{RRM}	Repetitive peak reverse voltage	$V_{RRM} tp=10ms$ $V_{RSM}=V_{RRM}+100V$		190	200		1000	V
I_{RRM}	Repetitive peak current	$V_{RM}=V_{RRM}$		190			50	mA
I_{FSM}	Surge forward current	10ms half sine wave		190			19	kA
I^2t	I^2T for fusing coordination	$V_R=0.6V_{RRM}$					1805	$A^2s \cdot 10^3$
V_{FO}	Threshold voltage			190			0.86	V
r_F	Forward slop resistance						0.165	m Ω
V_{FM}	Peak on-state voltage	$I_{FM}=3000A, F=18kN$		190			1.36	V
Q_{rr}	Recovery charge	$I_{FM}=2000A, tp=2000\mu s, di/dt=-20A/\mu s,$ $V_R=50V$		190		1900		μC
$R_{th(j-c)}$	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 18.0kN					0.028	$^{\circ}C/W$
$R_{th(c-h)}$	Thermal resistance case to heat sink						0.0075	
F_m	Mounting force				10		20	kN
T_{stg}	Stored temperature				-40		190	$^{\circ}C$
W_t	Weight					320		g
Outline	ZT39cT40							




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig.7




Fig.8

